




Uranus + Unequipped and Pre-assembled

Heating > Plate heat exchanger > Unequipped and Pre-assembled

2 YEAR WARRANTY

- + Compatible with all types of home heating (even low temperature)
- + Maximum robustness: titanium plates, new material for mounting flanges



URANUS Unequipped



URANUS pre-assembled

	UAN/UAP 35	UAN/UAP 70	UAN/UAP 120	UAN/UAP 240
PRODUCT REFERENCE				
Unequipped	WJ000001	WJ000003	WJ000005	WJ000007
Pre-assembled	WJ000002	WJ000004	WJ000006	WJ000008

EQUIPEMENTS URANUS + PRE-ASSEMBLED (UAP)

- Appliance completely assembled and wired
- High performance plate exchanger TITANIUM plates
- PRIMARY with adjustable accelerator 2 1/4 turn valves, 1 valve - male thread. Ø 26/34 with Ø 20/22 soldering cartridges
- SECONDARY - PVC Ø 50
- Digital display thermostat
- Flow switch. Flow switch
- Mono 230 V wiring from a mains outlet
- Purge or emptying cap

TECHNICAL SPECIFICATIONS

Power with primary at 90°C (kW)	55	80	120	240
Power with primary at 60°C (kW)	27	38	63	123
Power with primary at 45°C (kW)	15	21	34	68
Max. pressure (pool circuit)	3 bar / 2 bar			
Max. permitted temperature	90 °C / 40°C			
Electric power supply	230 V / 1 / 50 Hz			

CONNECTIONS

PRIMARY Heating (Unequipped model)	Ø20/22	Ø20/22	Ø20/22	Ø26/28
SECONDARY Pool	PVC Ø50	PVC Ø50	PVC Ø50	PVC Ø50

FLOW (m³/h)

PRIMARY Heating	1.6	2.1	2.8	6.3
SECONDARY Pool	2	2.9	4.3	8.7

LOAD LOSS (MCE)

PRIMARY Heating	1.5	1.2	1	2
SECONDARY Pool	2.4	2.3	2.5	3.8