



# Hydroxinator®

Water treatment > MagnaPool® > Hydroxinator®

- + Unrivalled swimming comfort
- + Crystal-clear water: clarifying effect of magnesium (Mg(OH)<sub>2</sub>), glass media
- + Eco-friendly: use less water and energy, fewer chemical additives
- + Upgradable: top-of-the-range unit with optional pH regulation module (pH Link).



**3** YEAR WARRANTY

UNCONDITIONAL WARRANTY UNCONDITIONAL



Product offered for sale on the «pool dealer» channel

	Hydroxinator® 10	Hydroxinator® 18	Hydroxinator® 22	Hydroxinator® 35
--	------------------	------------------	------------------	------------------

### PRODUCT REFERENCE

Standard model	WW000005	WW000006	WW000008	WW000009
----------------	----------	----------	----------	----------

### ACCESSORIES INCLUDED IN THE PACK

Wall mounting kit	Flow switch kit	Reducing bushes kit	AUS format plug

### FOR WHICH SWIMMING POOLS?

Volume of water treated (temperate climate, filtration 8hr/day)	40 m <sup>3</sup>	70 m <sup>3</sup>	100 m <sup>3</sup>	150 m <sup>3</sup>
Nominal chlorine production	10 g/hr	18 g/hr	25 g/hr	35 g/hr
Nominal output amperage	2.2	3.6	4.5	7.2

### DESCRIPTION

User interface	4-line, backlit LCD screen
Languages	7 (FR-EN-DE-ES-IT-NL-AF)
Operating modes	Normal, Boost (100%), Low (cover mode 10%)
Clock / Timer	24 hr clock / 2 timers
Polarity reversal	Yes: 2.5 or 5 hr (factory setting = 5hr)
Recommended minerals rate - minimum	5 g/L - 4.3 g/L minimum (*)
Safety features	'Minerals' indicator light: Production reduced to protect the electrode at low mineral levels 'No flow' indicator light: Production interrupted when conditions are not ideal Mechanical flow switch
Cell position	Horizontal
Compatible pipework	DN50 mm, DN63mm, 1½" (48 mm), 2" (61 mm)

(\*) Mineral levels are measured using the usual salinity testers.

ZPCE: recommended sales price valid from 01/01/2017 through 30/09/2017

Hydroxinator® 10



9 317545 014494

Hydroxinator® 18



9 317545 014500

Hydroxinator® 22



9 317545 014517

Hydroxinator® 35



9 317545 014524