



# MS - Media filter

Filtration > Filtres > MS

- + Easy to install
- + Efficient filtration
- + Easy maintenance

**NEW FOR 2019**







**3 YEAR**  
WARRANTY

**10 YEAR**  
WARRANTY  
ON TANK

Product offered for sale on the «pool dealer» channel

	MS 470	MS 530	MS 650	MS 800	MS 950
<b>PRODUCT REFERENCE</b>					
Standard model	WF000094	WF000095	WF000096	WF000097	WF000098

<b>ACCESSORIES INCLUDED IN THE PACK</b>			
			
"Classic" multiport valve kit	Pressure gauge & air relief kit	Bolts kit	Media filling cap

<b>DESCRIPTION</b>	
Tank material	Fiberglass reinforced polyester
Multiport valve	6-way side mount valve (filtration, backwash, rinse, drain, circulation, closed)
Pressure gauge position	Onto the top cover using a T-shape adaptor threaded into the lid
Connections	All connections are threaded for an easy maintenance (multiport valve & piping)
Drain	3/8" cm (water) / 2 1/2" (filter media, except for MS 470)

<b>TECHNICAL SPECIFICATIONS</b>					
Tank diameter (mm)	475	532	645	798	950
Max flow rate (m <sup>3</sup> /h)*	8.0	10.2	15.8	23.3	30.0
Filtering area (m <sup>2</sup> )	0.16	0.2	0.32	0.47	0.66
Diameter of threaded connections	1 1/2"			2"	
Total weight of Crystal Clear	75	90	135	270	435
Nbr of bags - Crystal Clear 1.0/3.0 mm	1		2	3	5
Nbr of bags - Crystal Clear 0.7/1.3 mm	4	5	7	15	17
Total weight of sand	85	100	160	310	485
Working pressure (bar or kg/cm <sup>2</sup> )	0,2 - 0,8 (variable speed pump); 0,4 - 1,4 (single speed pump)				
Maximum pressure (bar or kg/cm <sup>2</sup> )	2.5				

\* : For a 50 m<sup>3</sup>/h/m<sup>2</sup> filtration speed



MS 470



MS 530



MS 650



MS 800



MS 950

ZPCE: recZPCE: recommended sales price valid from 01/01/2019 through 31/12/2019