



Sirocco Through-the-wall

Dehumidification > Sirocco - Through-the-wall

2 YEAR
WARRANTY

- + Very easy to install through-the-wall
- + Available in 3 capacities (2.3 to 4.6 l/h)
- + "Air heating" option (electric heating or hot water battery)



	Sirocco through-the-wall 55 1-phase	Sirocco through-the-wall 80 1-phase	Sirocco through-the-wall 110 1-phase	Sirocco through-the-wall 110 3-phases
PRODUCT REFERENCE				
Standard model	W28SI55E	W28SI80E	W28SI110E	W28SI110ET
Model with electric heating option	W28SI55EE	W28SI80EE	W28SI110EE	W28SI110EET
	2 kW	3 kW	4,5 kW	4,5 kW
Model with hot water battery option	W28SI55EB	W28SI80EB	W28SI110EB	W28SI110EBT
	6 kW	9 kW	12 kW	12 kW

ACCESSORIES INCLUDED IN THE PACK



Hygro control box

TECHNICAL SPECIFICATIONS

Capacity (l/h)	2.3	3.3	4.6
Absorbed power* (W)	990*	1100*	1340*
Operating power* (W)	2080*	2310*	2810*
Acoustic pressure at 5m (dB(A))	600**	800**	1000**
Air flow (m3/h)	45.7	44.7	44.2
Electric power supply	230 V / 1 / 50 Hz		400 V / 3N / 50 Hz
Nominal operating intensity (A)***	4,45 ***	5,05 ***	6,35 ***
Max. absorbed intensity (A)***	5,9***	8 ***	9,8 ***
Refrigerant fluid	R407C		
Refrigerant fluid quantity (kg)	470	740	870
Evacuation of condensation	Flexible tube Ø12/18		

* Standard unit, in the following nominal conditions: air 30°C, humidity 70%.

** Values measured and certified in compliance with EN ISO 3741 & EN ISO 354 standards, by CCTM (Centre de Transfert de Technologie du Mans) on standard units.

*** excluding units featuring electrical heating option.