


Z200

Heating > Heatpump > Z200

- + The most compact
- + Guaranteed heating thanks to heating priority
- + Suits most pools



3 YEAR
WARRANTY

5 YEAR
CONDENSER
WARRANTY
ANTI-CORROSION

Product offered for sale on the «pool dealer» channel

	Z200 M2	Z200 M3	Z200 M4	Z200 M5
PRODUCT REFERENCE				
Standard model	WH000010	WH000011	WH000012	WH000013

ACCESSORIES INCLUDED IN THE PACK		
		
Winter cover	PVC fittings 1/2 unions 40 & 50	Anti-vibrations pads

EQUIPMENTS	
<ul style="list-style-type: none"> • Horizontal blowing • Polypropylene body • Digital display • Heating priority mode (filtration pump control) • Automatic defrosting (forced ventilation) • Anti-freeze thermostat (minimum operating temperature: +5°C) • HP & LP safety pressure switch 	<ul style="list-style-type: none"> • Water flow switch • Titanium water exchanger condenser • Rotary vane compressor • Capillary expansion valve • Refrigerant fluid: R410A

PERFORMANCE: AIR 28°C / WATER 28°C / HUMID. 80%				
Operating power (kW)	6.1	9	12	14.1
Consumed power (kW)	1.1	1.9	2.5	3
COP	5.6	4.7	4.8	4.7
PERFORMANCE: AIR 15°C / WATER 26°C / HUMID. 70%				
Operating power (kW)	4.6	6.3	8.4	10.2
Consumed power (kW)	1	1.6	2.1	2.6
COP	4.5		4.0	

TECHNICAL SPECIFICATIONS				
Recommended pool volume* (m ³)	0-30	20-45	30-60	40-70
Average water flow (m ³ /h)	3	4	5	
Hydraulic connection	PVC 1/2union, Ø 40 or 50, glued			
Electric power supply	230 V / 1 / 50 Hz			
Nominal operating power (A)	4.45	7.09	9.36	11.2
Maximum operating power (A)	5.2	8.7	12.4	15.7
Power cable size	3 x 2.5			
Refrigerant fluid quantity (g)	0.73	0.95	1.06	1.1
Acoustic pressure at 10m (dB(A))	38.2	39.1	40.6	43.7

*Estimated average values for a private pool with isothermal cover, from 15 May to 15 September.
**For a maximum length of 20 meters.